

Format view
Posted by codolt - 2015/06/29 10:26

Is it possible to change display format? For example data from database is like that: 20150629 and in table I want to display it as 2015/06/29

Re:Format view
Posted by admin - 2015/06/29 11:22

For example if you want to format value of publish_date column, the use the following SQL query:

```
SELECT
DATE_FORMAT(publish_date, '%Y/%m/%d') AS publish_date
...
```

or another solution if you want to format values from "created" field, set "Columns settings -> ID" parameter to created value and populate "Columns settings -> Format" parameter with the following value:

```
{ $value | regexreplace: #(\d\d\d\d)(\d\d)(\d\d):$1/$2/$3 }
```

Regards,
ARI Soft

Re:Format view
Posted by codolt - 2015/06/29 11:50

Thank you for quick response. But the thing is that if now I start search using '20150629' as keyword it says that there is no matches found. What I want is to display formatted data for users but for search use original data. I don't want to change the value of { \$value }. I just want to display it in different format for users. Is it possible?

Re:Format view
Posted by admin - 2015/06/29 11:57

If "ARI Data Table" widget is used ("Choose table type" parameter is set to "ARI Data Table") then it is possible to use the second solution from our previous post and set "Server side pagination" parameter to "Yes". Check that "System - ARI AJAX Dispatcher" plugin is installed and enabled.

Regards,
ARI Soft

Re:Format view
Posted by codolt - 2015/06/29 12:18

And without that there is no way to doing that? Because in my situation I cannot use "server side pagination".

Re:Format view

Posted by admin - 2015/06/29 12:30

Sorry, but it is not possible.

Regards,
ARI Soft

=====

Re:Format view

Posted by codolt - 2015/06/29 12:46

Then maybe it is possible to implement Type Based Search? I need to add columnDefs:

Inside

```
$('#example').dataTable( {  
    columnDefs:  
});
```

But I don't know where it is located in your plugin

=====

Re:Format view

Posted by admin - 2015/06/29 16:24

Javascript code for initialisation "DataTable" jQuery widget is generated in /modules/mod_aridatatables/includes/kernel/DataTables/Models/class.DataTablesWidgetDatatableModel.php file. See "initClientInstance" method.

Regards,
ARI Soft

=====