

---

## DataTable filter by urlid

Posted by soulxone - 2016/02/21 23:39

---

I have CRMERY plugin installed and have made many forms using rsforms.

I would like to display the form data entered by client only.

These datatables will load on 3 pages that have different url id's based on the page that is loading.

page 1 example i need the deal "id"

index.php?option=com\_crmary&view=deals&layout=deal&id=7&Itemid=290

Page 2 example I need the person "id"

index.php?option=com\_crmary&view=people&layout=person&id=43

Page 3 example I need the company "id"

index.php?option=com\_crmary&view=companies&layout=company&id=29

How can I get a MYSQL only statement to have the "ID" as my variable for all pages to start my datatables select statement.

I have been able to do this in rsform to populate a dropdown for each form to select the client from the company group of contacts. (code at bottom)

Thank you in advance for any help in the right direction with the URL ID capture SQL statement.

Shane

```
//
$url = RSFormProHelper::getURL();
$url= str_replace('http://app.plan-your-federal-
retirement.com/index.php?option=com_crmary&view=deals&layout=deal&id=', '', $url);

$items = array();
// Prepare the database connection
$db = JFactory::getDbo();
// Keep this if you'd like a "Please select" option, otherwise comment or remove it
$items = "|Please Select";

// Run the SQL query and store it in $results
$sql="SELECT CONCAT(first_name,' ',last_name) AS name
FROM `pyfr_crmary_people` WHERE company_id = (SELECT company_id FROM pyfr_crmary_deals WHERE id='$url')";
$db->setQuery($sql);
$results = $db->loadObjectList();

foreach ($results as $result) {
    $value = $result->name;
    $label = $result->name;
    $items = $value.'|'.$label;
}

$items = implode("\n", $items);

return $items;
//
```

=====

---

## Re:DataTable filter by urlid

Posted by admin - 2016/02/22 06:52

---

---

Hello,

If you want to use "id" request variable in "WHERE" clause of SQL query, a query will look like:

```
SELECT
id,
title
FROM
tbl
WHERE
({$REQUEST:id|empty:''} = '' || record_id = {$REQUEST:id|empty:''})
```

Regards,  
ARI Soft

=====

## Re:DataTable filter by urlid

Posted by soulxone - 2016/02/22 08:17

---

Thank you for this base code.

I have gotten this far.

```
SELECT
advisor_url_id_estateplanning,
advisor_clients_estateplanning
FROM
ninja_estateplanning
WHERE
({$REQUEST:'id'|empty:''} = '' || advisor_url_id_estateplanning = {$REQUEST:'id'|empty:''})
```

This has only made my datatable display ALL clients regardless of 'id'

Do I need to continue this statement to only display clients with the requested 'id'

Or how do I make it dynamically change the datatable view based on the 'id'

Sorry I missing something,

Shaen

=====

## Re:DataTable filter by urlid

Posted by admin - 2016/02/22 10:42

---

Remove quotes for 'id' parameter. It should be like in our sample query:

{\$REQUEST:id} instead of {\$REQUEST:'id'}

This feature works when "Server side pagination" parameter is set to "No".

Regards,  
ARI Soft

=====

## Re:DataTable filter by urlid

Posted by soulxone - 2016/02/25 00:02

---

---

Thank you,

Works great now,

Shane

=====